



Stainless Steel 316 Push-In Fittings

XMPUCS	MODEL(φ D)		XMPULS	MODEL(φ D)	
	Tube(Metric)	Tube(Inch)		Tube(Metric)	Tube(Inch)
	XMPUCS 04	XMPUCS 1/8		XMPULS 04	XMPULS 1/8
	XMPUCS 06	XMPUCS 5/32		XMPULS 06	XMPULS 5/32
	XMPUCS 08	XMPUCS 1/4		XMPULS 08	XMPULS 1/4
	XMPUCS 10	XMPUCS 5/16		XMPULS 10	XMPULS 5/16
	XMPUCS 12	XMPUCS 3/8		XMPULS 12	XMPULS 3/8
		XMPUCS 1/2			XMPULS 1/2

XMPUTS	MODEL(φ D)		XMPMS	MODEL(φ D)	
	Tube(Metric)	Tube(Inch)		Tube(Metric)	Tube(Inch)
	XMPUTS 04	XMPUTS 1/8		XMPMS 04	XMPMS 1/8
	XMPUTS 06	XMPUTS 5/32		XMPMS 06	XMPMS 5/32
	XMPUTS 08	XMPUTS 1/4		XMPMS 08	XMPMS 1/4
	XMPUTS 10	XMPUTS 5/16		XMPMS 10	XMPMS 5/16
	XMPUTS 12	XMPUTS 3/8		XMPMS 12	XMPMS 3/8
		XMPUTS 1/2			XMPMS 1/2

Metal Speed Controls


Feature

- Accurate regulation of an optimal air flow rate for Precise motion control.
- The compact design provides the comparable rang of speed as the larger standard Speed continue roller do.

Specification


Material	Body and collet:Nickel-plated Brass O-ring:NBR(other material is available on request)
Threads	BSPT,BSPP,NPT,Metric threads
Pressure Tube to connect	0.8-16bar(see tube)PU,PE,Nylon 6-11-12
Fluid	Compressed air
Temperature	-10℃~60℃(see data of used tubing)


When You order Control In Type,Pls Put BAT The End of Model Type,For Example:MNSE08-02B

XMNSE	MODEL(φ D-T)					
	Tube(Metric)-Thread(R)		Tube(Inch)-Thread(R)		Tube(Inch)-Thread(NPT)	
	XMNSE04-M5	XMNSE08-03	XMNSE1/8-01	XMNSE5/16-03	XMNSE1/8-U10	XMNSE1/4-N02
	XMNSE04-M6	XMNSE08-04	XMNSE1/8-02	XMNSE5-16-04	XMNSE1/8-N01	XMNSE1/4-n03
	XMNSE04-01	XMNSE10-01	XMNSE5/32-01	XMNSE3/8-01	XMNSE1/8-N02	XMNSE5/16-N01
	XMNSE04-02	XMNSE10-02	XMNSE5/32-02	XMNSE3/8-02	XMNSE5/32-U10	XMNSE5/16-N02
	XMNSE04-03	XMNSE10-03	XMNSE3/16-01	XMNSE3/8-03	XMNSE5/32-N01	XMNSE5/16-N03
	XMNSE06-M5	XMNSE10-04	XMNSE3/16-02	XMNSE3/8-04	XMNSE5/32-N02	XMNSE3/8-N01
	XMNSE06-M6	XMNSE12-01	XMNSE3/16-03	XMNSE1/2-02	XMNSE3/16-U10	XMNSE3/8-N02
	XMNSE06-01	XMNSE12-02	XMNSE1/4-01	XMNSE1/2-03	XMNSE3/16-N01	XMNSE3/8-N03
	XMNSE06-02	XMNSE12-03	XMNSE1/4-02	XMNSE1/2-04	XMNSE3/16-N02	XMNSE3/8-N04
	XMNSE06-03	XMNSE12-04	XMNSE1/4-03		XMNSE3/16-N03	XMNSE1/2-N02
	XMNSE08-01	XMNSE16-03	XMNSE5/16-01		XMNSE1/4-U10	XMNSE1/2-N03
	XMNSE08-02	XMNSE16-04	XMNSE5/16-02		XMNSE1/4-N01	XMNSE1/2-N04

Metal Speed Controls

XMNSE-G	MODEL(φ D-T)		XMNSP-G	MODEL(φ D-T)	
	Tube(Inch)-Thread(G)			Tube(Inch)-Thread(R)	
	XMNSE04-G01	XMNSE10-G02		XMNSP04-G01	XMNSE10-G02
	XMNSE04-G02	XMNSE10-G03		XMNSP04-G02	XMNSP10-G03
	XMNSE05-G01	XMNSE10-G04		XMNSP05-G01	XMNSP10-G04
	XMNSE05-G02	XMNSE12-G01		XMNSP05-G02	XMNSP12-G01
	XMNSE06-G01	XMNSE12-G02		XMNSP06-G01	XMNSP12-G02
	XMNSE06-G02	XMNSE12-G03		XMNSP06-G02	XMNSP12-G03
	XMNSE08-G01	XMNSE12-G04		XMNSP08-G01	XMNSP12-G04
	XMNSE08-G02	XMNSE14-G03		XMNSP08-G02	XMNSP14-G03
	XMNSE08-G03	XMNSE14-G04		XMNSP08-G03	XMNSP14-G04
	XMNSE08-G04	XMNSE16-G03		XMNSP08-G04	XMNSP16-G03
	XMNSE10-G01	XMNSE16-G04		XMNSP10-G01	XMNSP16-G04

XMNSP	MODEL(φ T)					
	Tube(Metric)-Thread(R)		Tube(Inch)-Thread(R)		Tube(Inch)-Thread(NPT)	
	XMNSP04-M5	XMNSP08-03	XMNSP1/8-01	XMNSP5/16-03	XMNSP1/8-U10	XMNSP1/4-N02
	XMNSP04-M6	XMNSP08-04	XMNSP1/8-02	XMNSP5-16-04	XMNSP1/8-N01	XMNSP1/4-N03
	XMNSP04-01	XMNSP10-01	XMNSP5/32-01	XMNSP3/8-01	XMNSP1/8-N02	XMNSP5/16-N01
	XMNSP04-02	XMNSP10-02	XMNSP5/32-02	XMNSP3/8-02	XMNSP5/32-U10	XMNSP5/16-N02
	XMNSP04-03	XMNSP10-03	XMNSP3/16-01	XMNSP3/8-03	XMNSP5/32-N01	XMNSP5/16-N03
	XMNSP06-M5	XMNSP10-04	XMNSP3/16-02	XMNSP3/8-04	XMNSP5/32-N02	XMNSP3/8-N01
	XMNSP06-M6	XMNSP12-01	XMNSP3/16-03	XMNSP1/2-02	XMNSP3/16-U10	XMNSP3/8-N02
	XMNSP06-01	XMNSP12-02	XMNSP1/4-01	XMNSP1/2-03	XMNSP3/16-N01	XMNSP3/8-N03
	XMNSP06-02	XMNSP12-03	XMNSP1/4-02	XMNSP1/2-04	XMNSP3/16-N02	XMNSP3/8-N04
	XMNSP06-03	XMNSP12-04	XMNSP1/4-03		XMNSP3/16-N03	XMNSP1/2-N02
	XMNSP08-01	XMNSP16-03	XMNSP5/16-01		XMNSP1/4-U10	XMNSP1/2-N03
	XMNSP08-02	XMNSP16-04	XMNSP5/16-02		XMNSP1/4-N01	XMNSP1/2-N04


XMNSR	MODEL(φ D-T)				XMNSF	MODEL(φ D)	
	Tube(Inch)-Thread(R)		Tube(Inch)-Thread(G)			Tube(Metric)	Tube(Inch)
	XMNSR-5/3-M5	XMNSR-8/6-03	XMNSR-5/3-G01	XMNSR-10/8-G04	XMNSF04	XMNSF1/8	
	XMNSR-5/3-M6	XMNSR-10/8-01	XMNSR-6/4-G01	XMNSR-12/10-G03	XMNSF06	XMNSF5/32	
	XMNSR-5/3-01	XMNSR-10/8-02	XMNSR-6/4-G02	XMNSR-12/10-G04	XMNSF08	XMNSF3/16	
	XMNSR-6/4-M5	XMNSR-10/8-03	XMNSR-6/4-G03		XMNSF10	XMNSF1/4	
	XMNSR-6/4-M6	XMNSR-10/8-04	XMNSR-8/6-G01		XMNSF12	XMNSF5/16	
	XMNSR-6/4-01	XMNSR-12/10-03	XMNSR-8/6-G02			XMNSF3/8	
	XMNSR-6/4-02	XMNSR-12/10-04	XMNSR-8/6-G03			XMNSF1/2	
	XMNSR-6/4-03		XMNSR-10/8-G01				
	XMNSR-8/6-01		XMNSR-10/8-G02				
	XMNSR-8/6-02		XMNSR-10/8-G03				

Rapid Fittings For The Plastic Tubings

Feature

- The rapid fittings can be used with rigid nylon tubes.
- A locking nut is provided and can be tightened both manually and With a spanner.
- The special shape of the guiding cone ensures that the tube can not be accidentally cut.

Construction



Specification

Material	Body and collet:Nickel-plated Brass O-ring:NBR(other material is available on request)
Threads	BSPT,BSPP,NPT,Metric threads
Pressure	0.8-16bar(see tube)
Fluid	Compressed air
Temperature	-10℃~60℃(see data of used tubing)